Analysis of Gas Turbine Blade with Number of Holes for Cooling

Ch. Indira Priyadarsini, T. Aasish Kashyap, K. Akshay Kumar, M. Dinesh Reddy, S.Vamshi Krishna

Abstract— The aim of the paper is to evaluate the need in the gas turbine industry for a systematic validated computational methodology for heat transfer problem to give the optimum cooling. Various techniques have been proposed for the cooling of blades and one such technique is to have axial holes along the blade span. Cooling of blades has been a major concern since they are in a high temperature environment. In a high temperature gas turbine, turbine blade cooling designs require key technologies. Computational fluid dynamic (CFD) is used to flow performance due to changing the material analvze properties of like Nickel-Chromium allov and Titanium-Aluminum Alloy. Three different models with different number of holes (6,8,12) were analyzed in this paper to find out the optimum number of holes for good cooling rate. In computational fluid dynamic (CFD),flow analysis is carried out. Graphs are plotted for velocity, pressure and temperature distribution for existing design. 3D model of the blade is shown. When the numbers of holes are increased in the blade, the temperature distribution falls down. Our calculations were compared adequately well with published experimental data as well as our own fundamental test data. Attention is focused on the accuracy using commercially available numerical methods, computational fluid dynamic (CFD) for fluid flow, temperature distribution for number of holes are analyzed.

Index Terms—Blade cooling, CFD, Gas Turbine, Flow analysis, Number of holes

I. INTRODUCTION

A turbine blade is the individual component which makes up the turbine section of a gas turbine. The blades are responsible for extracting energy from the high temperature, high pressure gas produced by the combustor. The turbine blades are often the limiting component of gas turbines. To survive in this difficult environment, turbine blades often use exotic materials like super alloys and many different methods of cooling, such as internal air channels, boundary layer cooling, and thermal barrier coatings. The number of turbine stages can have a great effect on how the turbine blades are designed for each stage. Many gas turbine engines are twin spool designs, meaning that there is a high pressure spool and a low pressure spool. Other gas turbines use three spools, adding an intermediate pressure spool between the high and low pressure spool. The high pressure turbine is exposed to the hottest, highest pressure air, and the low pressure turbine is subjected to cooler, lower pressure air. That difference in conditions leads the design of high pressure and low pressure turbine blades to be significantly different in material and cooling choices even though the aerodynamic and thermodynamic principles are the same.

II. LITERATURE

The existing literature contains many experimental and numerical investigations on flow field in and around turbine blade tip models. Studies by R Yadav [9] and S.Gowreesh[1] have contributed to the general understanding of tip leakage flow patterns. S.Gowreesh concluded that the growth of a vortex, which forms as the flow separates on the pressure side wall and exits through the tip gap causing an increase in the secondary flow, results in large aerodynamic losses. Han et al [3] worked on the topic of "Conjugate Heat Transfer Analysis Of Internally Cooled Gas Turbine Airfoils "performed two three-dimensional conjugate analysis of a radically and cooled gas turbine blade: the only thermal boundary conditions they imposed were the HTC on the surfaces of the internal coolant flow passages. Laskowski and Felten research first stage gas turbine blades by means of computational fluid dynamics simulations, and the effect of cooling fluid on the blades of the next stage of the study [2]. John D Denton's research focuses on the limitations of computational fluid dynamics and numerical analysis of errors that may be considered and studied [3]. Sagib Hameed and Manarvi Research study predicts the location of damage in gas turbine blades by the finite element method for computational fluid dynamics is discussed, as a reference for non-destructive testing used [4]. The purpose of turbine technology [1] are to extract the maximum quantity of energy from the working fluid to convert it into useful work with maximum efficiency by means of a plant having maximum reliability, minimum cost, minimum supervision and minimum starting time. Since the allowable temperature on the turbine blade dependents on the hot gas temperatures from the combustion chamber, preliminary design is been taken from the optimized dump gap design study carried out by Gowreesh.et.al [1]. The gas turbine obtains its power by utilizing the energy of burnt gases and the air which is at high temperature and pressure by expanding through the several ring of fixed and moving blades to get a high pressure of order 4 to 10 bar of working fluid which is essential for expansion. Blade metal temperature distribution and temperature gradients are the most important parameters determining blade life. Therefore, accurately predicting blade heat transfer parameters is essential for precisely predicting blade life. As mentioned above, one of the most important loads for calculating blade life is temperature distribution. In cooled turbines, in order to calculate blade temperature precisely, internal coolant, external hot gas, and metal conduction should be simulated simultaneously by conjugate heat transfer (CHT) method. There have been increased research efforts in applying the CHT methodology to simulate gas turbine blade heat transfer Although three-dimensional (3-D) modeling of vanes and blades with complex cooling passages is time-consuming, there are some studies [8–11] which used 3-D solver and CHT method to calculate the temperature distribution of vanes and blades with more complex internal cooling passages.

III. MATH MATERIALS & METHODOLOGY

If There are many types of cooling used in gas turbine blades; convection, film, transpiration cooling, cooling effusion, pin fin cooling etc. which fall under the categories of internal and external cooling. While all methods have their differences, they all work by using cooler air (often bled from the compressor) to remove heat from the turbine blades.



Fig.1 Types of cooling methods

The experimental techniques have their inherent problems viz. that they are equipment oriented, and they need large resources of hardware, time and operating costs. This approach forms the core of Computational Fluid Dynamics, commonly known as CFD. The popularity of CFD has been possible due to great developments in computing algorithms that have enabled fast Graphic User Interface that makes the interpretation and Visualization of the results easier.

Table 1 Material properties of Titanium-Aluminum alloy

	[2]			
Property	Values			
Density	4.51 g.cm ⁻³ at 20°C			
Poisson's Ratio	0.3			
Melting Point	1660 °C			
Specific Heat	520.J/(Kg K)			
Thermal Conductivity	7 W/ <u>m.K</u>			
Resistivity	42×10 ¹⁰ ohm.m			

Table 2 Material properties of Nickel-Chromium alloy[7]

Property	Values		
Density	8.9 g.cm ⁻³ at 20°C		
Poisson's Ratio	0.325		
Melting Point	1753 °C		
Specific Heat	445.J/(Kg K)		
Thermal Conductivity	17 W/ <u>m.K</u>		
Resistivity	699×10 ¹⁰ ohm.m		

IV. TUTBINE BLADE MODELLING

U Using GAMBIT software, modeling is created with given dimensions as shown in the Fig.2.



Fig.2 Schematic of the gas turbine blade

Three designs has been analyzed to observe the cooling pattern of turbine blades. The blade with holes of 6,8 and 12 were modeled using GAMBIT.



Fig. 3 Blade with 6 holes



Fig. 4 Blade with 8 holes



Fig. 5 Blade with 12 holes

CFD ANALYSIS

CFD Analysis has been performed using numerical flow simulation of FLUENT.

Meshing of gas turbine blade with different models

- The mesh is refined around the gas turbine blade to properly capture the boundary layer.
- Meshing is the process of discretization of space in which flow takes place.

Meshing is the basic step in building a computer model for a flow problem. Depending on the discretization technique used, meshing procedure varies



Fig. 6 Meshing of 6 holes gas turbine blade



Fig. 7 Meshing of 8 holes gas turbine blade



Fig.8 Meshing of 12 holes gas turbine blade

Boundary Conditions:

Table 3 Boundary conditions

Inlet pressure	160kPa
Inlet temperature	800°C
Inlet velocity	5m/s
Exit static pressure	110kPa
Inlet turbulence intensity	9%
Coolant temperature	300°C

V. RESULTS AND DISCUSSIONS

Contours of Nickel Chromium alloy with 6holes



Fig. 9 Variation of static pressure of 6 holes Nickel alloy in Gas Turbine blade.



Fig. 10 Variation of static temperature of 6 Holes Nickel alloy in Gas Turbine blade.

Contours of Titanium-Aluminum alloy with 6 holes



Fig. 11 Variation of static pressure of 6 holes Titanium alloy in Gas Turbine Blade.



Fig. 12 Variation of static Temperature of 6 Holes Contours of Nickel-Chromium alloy with 8 holes



Fig. 13 Variation of static pressure of 8 holes Nickel



Fig. 14Variation of static temperature of 8 Holes Nickel Contours of Titanium-Aluminum alloy with 8 holes







Fig.16Variation of static temperature of 8 holes Contours of Nickel-Chromium alloy with 12 holes







Fig.18 Variation of static temperature of 12 Holes Nickel alloy in Gas Turbine Blade.

Contours of Titanium aluminum alloy with 12 holes



Fig.19 Variation of static pressure of 12 holes Titanium alloy in Gas Turbine Blade.



Fig.20 Variation of static temperature of 12 holes

No. of Holes	Pressure(Pa)		Temperature(°C)	
	Titanium alloy	Nickel alloy	Titanium alloy	Nickel alloy
6	2.76e6	9.80e5	6.68e2	6.65e2
8	2.46e6	2.63e5	5.25e2	5.06e2
12	1.38e6	1.33e5	3.95e2	2.64e2

From the above results it is observed, when the number of holes increases pressure decreases, Nickel alloy gives the minimum pressure because Nickel alloy is better material than Titanium alloy. Pressure distribution depends on the material used for the blade and strength of the blade. Nickel alloy gives the minimum temperature because Nickel alloy is better material than Titanium alloy. Temperature depends on the material strength.

VI. CONCLUSION

- Using CFD analysis as a tool, the flow analysis is carried out sequentially.
- The blade with different no. of holes 6,8 and 12 were used for analysis. It was found that the blade with 8 holes has the moderate cooling rate for both materials of the blade when the coolant temperature was 300°C.

- The placement of cooling holes in the blades which resulted in increased turbine efficiency.
- ➤ The overall cooling rate is 20% from the both materials with 6 and 12 holes models.

REFERENCES

- G. S.Gowreesh, S., Sreenivasalu Reddy, N. and Yogananda Murthy, NV. 2009. Convective Heat Transfer Analysis of a Aero Gas Turbine Blade Using Ansys, *International Journal of Mechanics and Solids. 4:* 39-46.
- [2] B. Deepanraj, P. Lawrence and G. Sankaranarayanan, Theoretical Analysis Of Gas Turbine Blade By Finite Element Method, *Scientific World, Vol. 9, No. 9, July 2011*
- [3] Han, J. C., Dutta, S., and Ekkad, S. V., Gas Turbine Heat Transfer and Cooling Technology, Taylor and Francis.
- [4] Kirankumar K.M., Dr. Basawaraj, Heat Transfer Analysis Of Internally Cooled Gas Turbine Airfoils, Vol. 2, Issue 11, November 2013, Conjugate
- [5] Mohammad, H., Albeirutty., Abdullah, S., Alghamdi., Yousef, S. Najjar. 2004. Heat transfer analysis for a multi stage gas turbine using different blade-cooling schemes, *Applied Thermal Engineering*.24:563-577.
- [6] Giovanni, C., Ambra, G., Lorenzo, B. and Roberto, F. 2007 Advances in effusive cooling techniques of gas turbines, Applied Thermal Engineering. 27: 692-698.H. Poor, An Introduction to Signal Detection and Estimation. New York: Springer-Verlag, 1985, ch. 4.
- [7] V.Ganeshan, A Text Book of Gas Turbines.
- [8] Shridhar Paregouda1, Prof. Dr. T. Nageswara Rao,CFD Simulation on Gas turbine blade and Effect of Hole Shape on leading edge Film Cooling Effectiveness.
- [9] R.Yadav,"Steam and Gas turbine", Central Publishing House, Allahabad, 2003
- [10] Hidekazu Iwasaki, Koji Take Gas Turbine Research & Development Center, Gas Turbine & Machinery Company Kawasaki Heavy Industries, Ltd., Akashi, Japan, "Thermal and fluid analyses for gas turbine cooled vane and blade".
- [11] D.E. Bohn, C. Tummers, Numerical 3-D conjugate flow and heat transfer investigation of a transonic convection-cooled thermal barrier coated turbine guide vane with reduced cooling fluid mass flow, ASME Paper No. GT2003-38431,2003.
- [12] W.D. York, J.H. Leyek, Three-dimensional conjugate heat transfer simulation of an internally-cooled gas turbine vane, ASME Paper No. GT2003-38551, 2003.
- [13] J. Luo, E.H. Razinsky, Conjugate heat transfer analysis of a cooled turbine vane using the V2F turbulence model, ASME Journal of Turbo machinery 129 (4) (2007) 773–781.
- [14] Z.F. Wang, P.G. Yan, Z.Y. Guo, W.J. Han, BEM/FDM conjugate heat transfer analysis of a two-dimensional air-cooled turbine blade boundary layer, *Journal of Thermal Science* 17 (3) (2008) 199–206.

Ch.Indira Priyadarsini: M.Tech specialized in thermal engineering from JNTUH and doing Ph.D in Osmania University. Interested in IC engines, renewable energy, CFD and numerical methods.

T. Aasish Kashyap:B.Tech mechanical, interested in FEM, CFD and member of ASME student chapter

K. Akshay Kumar: B.Tech mechanical, interested in FEM, CFD and member of ASME student chapter

M. Dinesh Reddy: B.Tech mechanical, interested in FEM, CFD and member of ASME student chapter

S.Vamshi Krishna: B.Tech mechanical, interested in FEM, CFD and member of ASME student chapter